

**CHAPTER 28**

**STANDARDS FOR ISSUING PERMITS FOR COMMERCIAL OILFIELD WASTE  
DISPOSAL FACILITIES**

**Section 1. Authority.**

This rule is promulgated pursuant to the Wyoming Environmental Quality Act, Wyoming Statutes (W.S.) § 35-11-101 through § 35-11-2005, specifically W.S. § 35-11-301(a) (i), W.S. § 35-11-301(a)(iii), W.S. § 35-11-302(a)(iii), W.S. § 35-11-306, and W.S. § 35-11-307.

**Section 2. Applicability.**

(a) This Chapter contains the minimum standards for the design and construction of commercial oilfield waste disposal facilities that are required to obtain a permit under W.S. § 35-11-301(a)(iii), W.S. § 35-11-306, and Water Quality Rules and Regulations Chapter 3. In addition, this Chapter contains operation, monitoring, and reporting requirements for commercial oilfield waste disposal facilities.

(i) All applicants for a Water Quality Rules and Regulations Chapter 3 permit to construct, install, modify, or operate a commercial oilfield waste disposal facility shall meet all minimum standards of this Chapter.

(ii) No permit to construct, install, modify, or operate a commercial oilfield waste disposal facility shall be issued to a facility that does not meet the minimum standards of this Chapter.

(iii) All commercial oilfield waste disposal facilities shall be constructed, installed, and operated in accordance with permits issued pursuant to this Chapter.

(b) The installation of any component of a commercial oilfield waste disposal facility requires a permit to construct.

(c) Commercial oilfield waste disposal facilities are authorized to accept exempt exploration and production (E&P) wastes.

(i) Non-exempt, non-hazardous waste may be approved on a case-by-case basis, at the permittee's request.

(ii) The Division requires hazardous waste characteristic analysis of all non-exempt wastes proposed to be disposed of at a commercial oilfield waste disposal facility.

42 Additional sampling may be required by the Division based on the type of waste to be disposed.  
43 If any of the hazardous waste regulatory levels are exceeded, the wastes shall be disposed at a  
44 facility approved to accept hazardous wastes.

45  
46 (d) Pursuant to the provisions of W.S. § 35-11-109 (a)(ii) and W.S. § 35-11-  
47 1104(a)(iii), while subject to the requirements of the Wyoming Environmental Quality Act,  
48 noncommercial oilfield waste disposal facilities permitted by the Wyoming Oil and Gas  
49 Conservation Commission, are exempt from the requirements of this Chapter.

50

51 **Section 3. Timing of Compliance with These Regulations.**

52

53 Any facility covered by an individual permit issued pursuant to Water Quality Rules and  
54 Regulations, Chapter 3, prior to the effective date of this chapter shall remain covered under that  
55 permit. New construction or modification of existing permitted facilities must obtain  
56 authorization under a new permit, in accordance with Water Quality Rules and Regulations  
57 Chapter 3, Section 9(a)(iii), subject to the requirements of this Chapter.

58

59 **Section 4. Definitions**

60

61 (a) The definitions in this Section supplement those definitions contained in W.S. §  
62 35-11-103 of the Wyoming Environmental Quality Act.

63

64 (b) “Commercial oilfield waste disposal facility” (COWDF) means a facility that:

65

66 (i) Receives or has received produced water, exempt exploration and  
67 production waste, or non-hazardous non-exempt wastes approved by the Department, for  
68 treatment, storage, or disposal in pits, evaporation ponds, or surface impoundments; and

69

70 (ii) Receives or has received produced water, exploration and production  
71 waste, or other approved wastes from persons other than the owners and operators of the facility.

72

73 (c) “Exempt exploration and production (E&P) waste(s)” means drilling fluids,  
74 produced waters, and other wastewater associated with the exploration, development, or  
75 production of crude oil, natural gas or geothermal energy that are solid wastes but that are not  
76 identified as hazardous wastes under 40 CFR § 261.4(b)(5).

77

78 (d) “Groundwater” means subsurface water that fills available openings in rock or  
79 soil materials such that they may be considered water saturated under hydrostatic pressure.

80

81 **Section 5. Facilities and Systems not Specifically Covered by these Standards.**

82

83           (a) Each application for a permit to construct a facility under this section shall be  
84 evaluated on a case-by-case basis using the best available technology. The Water Quality  
85 Division (Division) may approve applications demonstrating the constructed facility can meet  
86 the purpose of the Act and this Chapter.

87  
88           (b) The following information shall be included with the application for a permit to  
89 construct, install, modify, or operate a commercial oilfield waste disposal facility not specifically  
90 covered by these standards:

91  
92                   (i) Data obtained from a full scale, comparable installation that demonstrates  
93 the acceptability of the design; or

94  
95                   (ii) Data obtained from a pilot plant operated under the design condition for a  
96 sufficient length of time to demonstrate the acceptability of the design; or

97  
98                   (iii) Data obtained from a theoretical evaluation of the design demonstrates a  
99 reasonable probability that the facility will meet the design objectives.

100  
101                   (iv) An evaluation of the flexibility of making corrective changes to the  
102 constructed facility in the event it does not function as planned.

103  
104           (c) If an applicant wishes to construct a pilot plant to provide the data necessary to  
105 meet the requirements of this Section, then the applicant must obtain a permit to construct.

106  
107           **Section 6. Site Suitability.**

108  
109           (a) The applicant shall demonstrate that the proposed facility location complies with  
110 W.S. § 35-11-306(a)(i)-(ii).

111  
112           (b) Additionally, the applicant shall demonstrate that the proposed facility location:

113  
114                   (i) Is positioned so that the depth to highest seasonal groundwater is at least  
115 five (5) feet below the secondary liner;

116  
117                   (ii) Is outside of the 100-year floodplain of surface waters of the State; and

118  
119                   (iii) Is not within ephemeral drainages into which natural runoff may flow or  
120 enter.

121  
122           **Section 7. Permits, Permit Application, and Recordkeeping Requirements.**

124           (a) Applications for a permit to construct, install, modify, or operate a commercial  
125 oilfield waste disposal facility shall meet the requirements of Water Quality Rules and  
126 Regulations Chapter 3, Section 6.

127  
128           (b) The application shall:

129  
130                   (i) Include signatures of:

131  
132                           (A) The surface estate owner of record or legal designee authorizing  
133 legal access, or documentation of right of way in cases of state or federal land ownership; and

134  
135                           (B) The operator.

136  
137                   (ii) Include the following components:

138  
139                           (A) An engineering design report that meets the requirements of  
140 Section 9 of this Chapter;

141  
142                           (B) A construction plan that meets the requirements of Section 10 of  
143 this Chapter;

144  
145                           (C) Monitoring and reporting that meet the requirements of Section 11  
146 of this Chapter;

147  
148                           (D) An operation and maintenance plan that meets the requirements of  
149 Section 12 of this Chapter; and

150  
151                           (E) Closure and post-closure plans that meet the requirements of Water  
152 Quality Rules and Regulations Chapter 14, Section 3 and a corrective action plan that meets the  
153 requirements of Water Quality Rules and Regulations Chapter 14, Section 4.

154  
155                   (iii) Be submitted to the Division in a format required by the Administrator,  
156 including plans, specifications, design data, or other pertinent information covering the project,  
157 and any additional information required by the Administrator.

158  
159                   (iv) Include certification under penalty of perjury that the applicant has  
160 secured and will maintain permission for Department personnel and their invitees to access the  
161 facility, including permission to:

162  
163                           (A) Access the land where the facility is located;

- 164  
165                   (B) Collect resource data as defined by W. S. § 6-3-414; and  
166  
167                   (C) Enter and cross all properties necessary to access the facility if the  
168 facility cannot be directly accessed from a public road.

169                   **Section 8. Annual Reporting Requirements**

170  
171  
172                   (a) The permittee shall submit to the Division by April 1 of each year an annual  
173 report that includes:

174  
175                   (i) The name of the facility, the Division issued COWDF identification  
176 number, the name of the owner, the reporting contact, and permit numbers for the facility;

177  
178                   (ii) Description of any modification and operation details of the facility from  
179 the previous year, any anticipated construction, modification, or operational changes for the  
180 upcoming year;

181  
182                   (iii) A discussion and analysis of the groundwater monitoring results, including  
183 a graph of the last five (5) years of data in a format approved by the Administrator;

184  
185                   (iv) A discussion and analysis of the leak detection monitoring results and any  
186 corrective actions taken;

187  
188                   (v) Annual sampling results of evaporation ponds;

189  
190                   (vi) The annual revised cost estimates for closure, post-closure, and corrective  
191 action, and the financial assurance instruments that are required in Water Quality Rules and  
192 Regulations Chapter 14, Sections 3 and 4; and

193  
194                   (vii) Wastewater transfer records, as required by Section 11(g) of this Chapter.

195  
196                   (b) Reporting requirements are subject to modification by the Administrator.

197  
198                   **Section 9. Engineering Design Report.**

199  
200                   (a) An engineering design report is required for each permit application and shall  
201 include:

202  
203                   (i) A description of the facility site and location including:  
204

- 205                            (A) The legal description of the present and projected facility property  
206 boundary, including existing and proposed buildings and facilities; and  
207  
208                            (B) The surface and mineral owner(s) of record.  
209  
210                   (ii) A geotechnical report for the proposed site that includes:  
211  
212                            (A) Groundwater information, including the depth to groundwater;  
213  
214                            (B) A summary of all subsurface investigations;  
215  
216                            (C) A subsurface soil profile;  
217  
218                            (D) Exploration logs;  
219  
220                            (E) Laboratory or in-situ test results;  
221  
222                            (F) Interpretation and analysis of subsurface investigations;  
223  
224                            (G) Specific engineering recommendations for design; and  
225  
226                            (H) Solutions or discussion of anticipated problems.  
227  
228                   (iii) A detailed description of the types of waste(s) to be accepted at the facility  
229 that includes, but is not limited to, the following:  
230  
231                            (A) Produced water;  
232  
233                            (B) Well completion and stimulation products;  
234  
235                            (C) Wastes from production separators;  
236  
237                            (D) Gas plant dehydration wastes;  
238  
239                            (E) Gas plant sweetening wastes; and  
240  
241                            (F) A list of anticipated generators of the waste(s);  
242  
243                   (iv) A description of design conditions that includes:  
244  
245                            (A) Identification of required performance characteristics of all  
246 construction materials;  
247  
248                            (B) The type, size, strength, operating characteristics, rating or  
249 requirements for all;  
250

- 251 (I) Mechanical and electrical equipment;  
252  
253 (II) Laboratory fixtures and equipment;  
254  
255 (III) Operating tools; and  
256  
257 (IV) Chemicals (where used).  
258  
259 (C) Construction and installation procedures;  
260  
261 (D) Testing requirements to ensure materials and equipment meet  
262 design standards;  
263  
264 (E) Waste treatment, storage, and disposal methods; and  
265  
266 (F) Summary of operation procedures.  
267  
268 (v) A geologic report, signed and sealed by a Wyoming Professional  
269 Geologist in accordance with W.S. § 33-41-115(c), that includes:  
270  
271 (A) A stratigraphic column that illustrates the thickness and geologic  
272 names of alluvial materials and geologic formations that comprise the unsaturated, or vadose,  
273 zone;  
274  
275 (B) A description of the lithology and hydraulic conductivity of  
276 materials and geologic formations comprising the unsaturated zone, the first encountered  
277 groundwater, and the uppermost aquifer underlying the proposed facility;  
278  
279 (C) A potentiometric map of the uppermost water bearing zone  
280 beneath the facility that:  
281  
282 (I) Illustrates the locations and use of all wells within one (1)  
283 mile of the proposed facility, clearly identifying those wells producing in whole, or in part, from  
284 the uppermost water bearing zone, and including project borings or wells; and  
285  
286 (II) Includes a description of the uppermost aquifer in terms of  
287 its relative confinement, permeability, and porosity.  
288  
289 (vi) Documentation that the proposed facility will comply with Water Quality  
290 Rules and Regulations Chapter 3, Section 18;  
291  
292 (vii) A sampling and analysis plan that satisfies the monitoring requirements of  
293 Section 11 of this Chapter; and  
294  
295 (viii) Details of the leak detection system that satisfies the requirements of  
296 Section 11 of this Chapter.

- 297  
298 (b) Engineering design drawings are required for each permit application and shall  
299 include:  
300  
301 (i) On each page:  
302  
303 (A) A suitable title block that includes the applicant's name, facility  
304 name, and Division assigned COWDF identification number, and the revision date and number;  
305 and  
306  
307 (B) The seal and signature of the Wyoming Professional Engineer.  
308  
309 (ii) A plan set that includes:  
310  
311 (A) A scaled site plan; and  
312  
313 (B) A cover sheet with an index as the first page of each plan set.  
314  
315 (iii) The following components:  
316  
317 (A) North arrow and drawing scale;  
318  
319 (B) Legend;  
320  
321 (C) Fencing and security;  
322  
323 (D) Topographic features and contours with indicated datum;  
324  
325 (E) Soil and subsurface geological characteristics;  
326  
327 (F) Location of soil borings, bedrock elevations, and seasonal high  
328 groundwater elevations;  
329  
330 (G) Locations and dimensions of piping, including those in and under  
331 buildings;  
332  
333 (H) The location of all cross-sections and profiles, which shall be  
334 identified in the plan views;  
335  
336 (I) Locations of buildings, evaporation ponds, pits, tanks, utilities, and  
337 roads;  
338  
339 (J) Scaled geologic cross-sections with the evaporation ponds'  
340 geometry, monitoring wells, borings, and groundwater observations (if present) superimposed on  
341 the geologic cross-sections;  
342



343 (K) Present and proposed access, including a map of the access  
344 route(s) to the facility from the nearest public road;

345  
346 (L) The distances to occupied dwelling buildings or school buildings;  
347 and

348  
349 (M) Prevailing wind direction.

350

351 **Section 10. Minimum Design and Construction Standards.**

352

353 (a) Receiving facility and phase separation facility designs shall meet the following  
354 standards:

355

356 (i) Liquid hydrocarbons shall be removed from wastewater before it is  
357 discharged to the evaporation ponds.

358

359 (ii) All open-topped tanks in the receiving facility and the phase separation  
360 facility shall be covered with netting, screen, or other approved method to prevent the entry of  
361 birds and other wildlife.

362

363 (A) The netting, screen, or approved covering shall be constructed to  
364 remain intact and above the surface of the liquid in the tank even during winds up to eighty (80)  
365 mph, or when weighted with snow, ice, or rain.

366

367 (b) To protect birds and other wildlife, evaporation ponds shall be kept virtually oil  
368 free at all times or shall be completely netted or screened to the standards required for open-  
369 topped tanks.

370

371 (i) Hydrocarbon sheen on any part of the evaporation ponds shall be removed  
372 immediately.

373

374 (c) The facility design shall meet the following earthwork standards:

375

376 (i) For evaporation ponds specified to be lined with a geomembrane liner:

377

378 (A) Rocks larger than six (6) inches in length shall not be placed within  
379 five (5) feet of the interior slope of any evaporation pond embankment. All rocks and other  
380 material that could damage the geomembrane shall be removed from the surface to be covered  
381 with the geomembrane;

382

383 (B) Material containing by volume less than twenty-five (25%) percent  
384 of rock larger than six (6) inches and less than twelve (12) inches in length may be placed in the  
385 remainder of the embankment.

386  
387 (ii) Outer dike slopes shall not be steeper than a ratio of one (1) vertical to  
388 three (3) horizontal in order to prevent surface runoff from entering the evaporation ponds. The  
389 Administrator may require flatter slopes to maintain slope stability.

390  
391 (iii) Inner dike slopes shall be between a ratio of one (1) vertical to four (4)  
392 horizontal and one (1) vertical to three (3) horizontal.

393  
394 (iv) The minimum top dike width shall be twelve (12) feet to allow access to  
395 maintenance vehicles. Top dikes wider than twelve (12) feet shall be required when necessary to  
396 ensure structural stability.

397  
398 (v) Freeboard design shall comply with the following requirements:

399  
400 (A) The minimum freeboard at the maximum operating level shall be  
401 three (3) feet.

402  
403 (B) In order to prevent unauthorized discharges to the air, land or  
404 Waters of the State, the Administrator may require increased freeboard, on a case-by-case basis,  
405 in order to compensate for wave action due to evaporation pond design, meteorological, or  
406 topographic conditions that may exceed the proposed freeboard.

407  
408 (d) The facility design shall meet the following liner base, primary and secondary  
409 liner, and leak detection system standards:

410  
411 (i) All evaporation ponds shall be constructed with a compacted clay  
412 secondary liner base or a geosynthetic clay secondary liner base that is contoured to include  
413 individual sub-cells that can be isolated if a leak is detected, as required in Section  
414 10(d)(iv)(C)(I).

415  
416 (A) Compacted clay secondary liner bases shall be a minimum of one  
417 (1) foot thick with a maximum permeability of  $1 \times 10^{-5}$  cm/sec and shall be constructed with  
418 maximum compacted lifts of one-half (1/2) foot.

419  
420 (I) Tests for water content and density shall be taken during  
421 the placement of each lift of the liner base.

422

423 1. Either permeability testing of undisturbed core  
424 samples from the in-place seal or detailed tests such as particle size distribution and Atterberg  
425 limits shall be conducted.

426  
427 2. Detailed tests shall confirm that the soil specified  
428 was used for liner construction. One (1) test shall be conducted per acre per lift. For core  
429 sampling of the in-place liner, one (1) core of the completed liner shall be tested per acre.

430  
431 3. The permittee shall provide the Division a written  
432 certification by a Wyoming Professional Engineer that the base was constructed according to the  
433 permit and that final testing indicated results within the allowable limits established by the  
434 permit.

435  
436 (II) For compacted clay secondary liner bases, a method of  
437 maintaining the seal at or above optimum moisture conditions is required.

438  
439 (B) Geosynthetic clay secondary liner bases installed according to the  
440 manufacturer's instructions are acceptable, provided that:

441  
442 (I) Geosynthetic clay liner bases shall have a maximum  
443 hydraulic conductivity of  $1 \times 10^{-8}$  cm/sec;

444  
445 (II) The manufacturer of the geosynthetic clay liner base shall  
446 have more than ten million square feet of their product installed;

447  
448 (III) The geosynthetic clay liner base installation contractor  
449 shall be approved by the manufacturer; and

450  
451 (IV) Geosynthetic clay liners that are used as secondary liner  
452 bases require surface erosion and abrasion protection and shall be protected during installation  
453 consistent with the manufacturer's requirements. If interior pond slopes steeper than 3:1  
454 horizontal to vertical are proposed, the factor of safety for slope failure on the composite liner  
455 shall be shown to be at least 1.5:1.

456  
457 (C) Handling, installation, and testing of geosynthetic clay liners shall  
458 be in accordance with the following specifications:

459  
460 (I) ASTM D5887/D5887M-16;

461  
462 (II) ASTM D5888-19;

- 463  
464 (III) ASTM D5889/D5889M-18;  
465  
466 (IV) ASTM D5890-19;  
467  
468 (V) ASTM D5891/D5891M-19;  
469  
470 (VI) ASTM D5993-18;  
471  
472 (VII) ASTM D6072/D6072M-19;  
473  
474 (VIII) ASTM D6102-15;  
475  
476 (IX) ASTM D6243/D6243M-16;  
477  
478 (X) ASTM D6788-02(2017);  
479  
480 (XI) ASTM D6495/D6495M-18;  
481  
482 (XII) ASTM D6768/D6768M-19;  
483  
484 (XIII) ASTM D6496/D6496M-19;  
485  
486 (XIV) ASTM D6243; and  
487  
488 (XV) GRI GCL3.

489  
490 (ii) All evaporation ponds shall be constructed with a high-density  
491 polyethylene (HDPE) geomembrane secondary liner that shall have a minimum thickness of 40  
492 mils.

493  
494 (A) HDPE geomembrane liners that conform to Geosynthetic  
495 Research Institute Standard Specification GRI-GM13, are acceptable.

496  
497 (B) Handling, installation, and testing of HDPE liners shall be in  
498 accordance with the following specifications:

- 499  
500 (I) GRI GM13;  
501  
502 (II) GRI GM9;

- 503  
504 (III) ASTM D751-19;  
505  
506 (IV) ASTM D792-13;  
507  
508 (V) ASTM D814-95(2020);  
509  
510 (VI) ASTM D882-18;  
511  
512 (VII) ASTM D1004-13;  
513  
514 (VIII) ASTM D1203-16;  
515  
516 (IX) ASTM D1204-14;  
517  
518 (X) ASTM D1505-18;  
519  
520 (XI) ASTM D1593-19;  
521  
522 (XII) ASTM D1603-14;  
523  
524 (XIII) ASTM D1790-14;  
525  
526 (XIV) ASTM D3895-19;  
527  
528 (XV) ASTM D4218-15;  
529  
530 (XVI) ASTM D4833/D4833M-07(2013);  
531  
532 (XVII) ASTM D5199-12(2019);  
533  
534 (XVIII) ASTM D5321/D5321M-20;  
535  
536 (XIX) ASTM D5397-19a;  
537  
538 (XX) ASTM D5596-03(2016);  
539  
540 (XXI) ASTM D5721-08(2018);  
541  
542 (XXII) ASTM D5885/D5885M-17;

543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582

(XXIII) ASTM D5994/D5994M-10(2015)e1;

(XXIV) ASTM D6392-12(2018);

(XXV) ASTM D6497/D6497M-02(2015)e1;

(XXVI) ASTM D6693/D6693M-04(2015)e1;

(XXVII) ASTM D7466/D7466M-10(2015)e1; and

(XXVIII) ASTM D7238-06(2017)07/01/2017.

(C) The liner manufacturer shall have more than ten million square feet of their product installed.

(D) Geomembrane liners installed and operated according to this Section shall not allow a discharge to groundwater by direct or indirect discharge, percolation or infiltration.

(iii) All evaporation ponds shall be constructed with a leak detection system that when installed, shall allow monitoring as required in Section 11(b) of this Chapter.

(iv) The leak detection system shall include drainage layers between the primary and secondary liners that shall have a minimum hydraulic transmissivity of one (1) gpm/foot.

(A) Synthetic drainage media may be used.

(B) The drainage layer shall have a minimum grade of four-tenths of one percent (0.4 %).

(C) Perforated or slotted collection lines shall be installed in the drainage layer arranged to create sub-cells with a maximum area of two (2) acres or less.

(I) Collection lines shall be configured to isolate sub-cells in the collection system for the purpose of locating leaks.

(II) No portion of the drainage layer shall be more than 140 feet from a collection line.

583  
584                   (D) The collection lines shall drain to a sump contained by the  
585 secondary liner.

586  
587                   (I) The sump shall be designed so that the maximum high  
588 liquid level during operating conditions is below the invert of any collection line discharging to  
589 the sump.

590  
591                   (II) The sump shall be large enough to allow a pump to be  
592 installed to remove all fluid from the sump.

593  
594                   (v) All evaporation ponds shall be constructed with a primary liner that shall  
595 be an HDPE geomembrane liner with a minimum thickness of sixty (60) mils.

596  
597                   (A) HDPE geomembrane liners shall conform to Geosynthetic  
598 Research Institute Standard Specification GRI-GM13;

599  
600                   (B) Handling, installation, and testing of HDPE liners shall meet the  
601 requirements of paragraph (d)(ii)(B) of this Section;

602  
603                   (C) The liner manufacturer shall have more than ten million square feet  
604 of their product installed;

605  
606                   (D) Geomembrane liners installed and operated according to this  
607 subparagraph shall not allow a discharge to groundwater by direct or indirect discharge,  
608 percolation, or filtration.

609  
610                   **Section 11. Monitoring and Reporting Requirements.**

611  
612                   (a) All applications for a permit to construct shall include:

613  
614                   (i) Documentation that demonstrates the groundwater monitoring wells  
615 comply with the construction standards of Water Quality Rules and Regulations Chapter 26;

616  
617                   (ii) Either the information required by Water Quality Rules and Regulations  
618 Chapter 3, Section 17(a) or the information required by Water Quality Rules and Regulations  
619 Chapter 3, Section 17(b)(ii) through (viii);

620  
621                   (iii) The ambient groundwater quality information for all monitoring wells for  
622 the Department to use to determine the groundwater class of use;

623

624 (A) The monitoring wells shall be sampled and tested prior to any  
625 wastewater disposal into the evaporation ponds; and

626  
627 (B) The monitoring wells shall be sampled and tested one (1) time for  
628 the parameters listed in Water Quality Rules and Regulations, Chapter 8, Table 1.

629  
630 (iv) A groundwater monitoring program as required by Water Quality Rules  
631 and Regulations Chapter 3, Section 17(d) and (e), and plans for record-keeping and reporting.

632  
633 (v) The operational monitoring plan shall include a sampling and analysis  
634 plan for each evaporation pond.

635  
636 (A) The sampling and analysis plan shall identify the evaporation pond  
637 locations and the methodology to be used to conduct monitoring at the evaporation ponds; and

638  
639 (B) The analyte list and monitoring frequency are subject to revision as  
640 required by the Administrator.

641  
642 (b) After approval by the Administrator, the monitoring program shall be  
643 incorporated as a permit condition to ensure compliance with Water Quality Rules and  
644 Regulations Chapter 8, Section 4(d)(v)(A) and Section 4(d)(vi)(A).

645  
646 (c) All monitoring shall be conducted in accordance with an Administrator-approved  
647 sampling and analysis plan. The sampling and analysis plans shall be included as part of the  
648 operation and maintenance (O&M) Plan.

649  
650 (d) Leak detection system monitoring.

651  
652 (i) The leak detection system's inspection pipes shall be inspected weekly for  
653 the first month and monthly thereafter.

654  
655 (ii) The permittee shall keep a log of the inspection results. If fluid is found:

656  
657 (A) The permittee shall notify the Administrator within twenty-four  
658 (24) hours of discovery.

659  
660 (B) The operator shall obtain samples from the inspection pipes and  
661 the evaporation cell(s) that have been tested, in accordance with US EPA SW-846, for total  
662 petroleum hydrocarbons (TPH) (modified for gasoline and diesel range hydrocarbons), chlorides,  
663 total dissolved solids (TDS) and sulfates.

664  
665 (C) The permittee shall report the sample results to the Administrator  
666 as soon as they are available.

667  
668 (e) Within ten (10) days of discovering a leak or fluid in the leak detection system,  
669 the permittee shall submit a plan and schedule to investigate the leak and repair the liner.



670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713

(f) Facilities that transfer wastewater shall:

(i) Maintain written records of all wastewater transfers that include:

(A) The date(s) of transfer;

(B) The volume of wastewater to be transferred;

(C) A description of the method of transfer;

(D) A copy of the written agreement(s) between the facility and the receiving parties that will be accepting the wastewater for reuse that identifies:

(I) The name, address, legal description by latitude and longitude, and telephone number for the receiving party;

(II) The receiving party's intended use of the transferred wastewater; and

(III) The location(s) where the wastewater will be applied or reused.

(ii) Maintain onsite all records required in this section and make the records available to Division representatives upon request. All records shall be compiled in an approved format and shall be included in the annual report, as required by Section 8(a)(vii) of this Chapter;

**Section 12. Operation and Maintenance Plan.**

(a) An operation and maintenance (O&M) plan is required for each new or modified facility and shall include the following information:

(i) An introduction that includes an overview of the facility and operational processes;

(ii) Process flow diagram;

(iii) Wastewater receiving procedures, including procedures for refusing loads that may not conform to permit requirements or facility policies;

(iv) Copies of all state and federal permits associated with the facility;

(v) Record keeping and reporting procedures;

714 (vi) Planned work and facility operation schedules;

715

716 (vii) Staffing and management structure;

717

718 (viii) Maintenance and inspection procedures;

719

720 (ix) Sampling and analysis plans for groundwater monitoring, evaporation  
721 pond monitoring, and leak detection system monitoring; and

722

723 (ix) A contingency plan that includes:

724

725 (A) A discussion of how hazards to human health and the environment  
726 will be minimized in case of fires, explosions, or unplanned sudden or non-sudden release of  
727 waste or waste constituents to soil, surface water, or groundwater;

728

729 (B) Procedures for notifying appropriate State or local agencies with  
730 designated response roles; and

731

732 (C) Reporting thresholds, response procedures, and recordkeeping  
733 requirements for spills, fires, explosions, and other possible failures.

734

735 (b) The O&M plan shall be submitted to the Division prior to fifty (50 %) percent  
736 completion of construction. Administrator approval of the final O&M plan is required prior to  
737 any water disposal into evaporation ponds.

738

739 **Section 13. Public Participation, Public Notice, and Public Hearing**  
740 **Requirements.**

741

742 (a) The Administrator shall give public notice for any of the following actions:

743

744 (i) The Administrator has prepared a draft permit that is intended for  
745 issuance.

746

747 (ii) The Administrator intends to modify a permit.

748

749 (iii) The Department intends to schedule a hearing.

750

751 (b) The Administrator shall include a thirty (30) day public comment period for any  
752 action on items (a)(i), or (a)(ii) of this Section, and shall provide at least thirty (30) days' public  
753 notice before any hearing held pursuant to paragraph (a)(iii) of this Section.

754

- 755 (c) Public notice shall be given by:  
756  
757 (i) Mailing a copy of the notice to the applicant, by certified or registered  
758 mail.  
759  
760 (ii) Mailing a copy of the notice to the following:  
761  
762 (A) Bureau of Land Management;  
763  
764 (B) Wyoming Oil and Gas Conservation Commission;  
765  
766 (C) Wyoming Game and Fish Department;  
767  
768 (D) Wyoming State Engineer; and  
769  
770 (E) Any unit of local government having jurisdiction over the area  
771 where the facility is proposed to be located.  
772  
773 (iii) Electronic notification of the notice to those individuals that subscribe to  
774 the Division's electronic notification list;  
775  
776 (iv) Publication of the notice in a newspaper of general circulation in the  
777 location of the facility or operation.  
778  
779 (d) All public notices issued under this Chapter shall contain the following minimum  
780 information:  
781  
782 (i) Name and address of the Department;  
783  
784 (ii) Name and address of the permittee or permit applicant, and, if different, of  
785 the facility or activity regulated by the permit;  
786  
787 (iii) A brief description of the business conducted at the facility or activity  
788 described in the permit application or the draft permit;  
789  
790 (iv) Name, address and telephone number of a person from whom interested  
791 persons may obtain further information, including, where applicable, copies of the draft permit,  
792 statement of basis, fact sheet, and the application;  
793  
794 (v) A brief description of comment procedures, procedures to request a  
795 hearing; and  
796

797 (vi) Any additional information required by the Administrator.

798

799 (e) In addition to the information required in paragraph (d) of this Section, any notice  
800 for a public hearing shall contain the following:

801

802 (i) Reference to the date of previous public notices relating to the permit;

803

804 (ii) Date, time and place of the hearing; and

805

806 (iii) A brief description of the nature and purpose of the hearing.

807

808 (f) The Department shall provide an opportunity for the applicant, permittee, or any  
809 interested person to submit written comments regarding permit issuance, modification, or to  
810 request a public hearing.

811

812 (g) During the public comment period, any interested person may submit written  
813 comments on the draft permit and may request a public hearing, in writing to the Administrator  
814 and shall state the reasons for the request.

815

816 (h) The Director shall render a decision on the draft permit within thirty (30) days  
817 after completion of the comment period if no hearing is requested. If a hearing is held, the  
818 Director shall make a decision on any Department hearing as soon as practicable after receipt of  
819 the transcript or after the expiration of the time set to receive written comments.

820

821 (i) At the time a final decision is issued, the Department shall respond, in writing, to  
822 those comments received during the public comment period and comments received during the  
823 allotted time for a hearing held by the Department. This response shall:

824

825 (i) Specify any changes that have been made to the permit; and

826

827 (ii) Briefly describe and respond to all comments that express a regulatory  
828 concern within the authority of the Department to regulate.

829

830 (j) The response to comments shall be available to the public.

831

832 **Section 14. Incorporation by Reference.**

833

834 (a) The following codes, standards, rules, and regulations referenced in this Chapter  
835 are incorporated by reference:

836

837 (i) ASTM International Standard D1004-13, *Standard Test Method for Tear*  
838 *Resistance (Graves Tear) of Plastic Film and Sheeting*, April 1, 2013, referred to as “ASTM  
839 D1004-13”;

840  
841 (ii) ASTM International Standard D1203-16, *Standard Test Methods for*  
842 *Volatile Loss from Plastics Using Activated Carbon Methods*, April 1, 2016, referred to as  
843 “ASTM D1203-16”;

844  
845 (iii) ASTM International Standard D1204-14, *Standard Test Method for Linear*  
846 *Dimensional Changes of Nonrigid Thermoplastic Sheeting or Film at Elevated Temperature*,  
847 March 1, 2014, referred to as “ASTM 1204-14”;

848  
849 (iv) ASTM International Standard D1505-18, *Standard Test Method for*  
850 *Density of Plastics by the Density-Gradient Technique*, May 10, 2018, referred to as “ASTM  
851 D1505-18”;

852  
853 (v) ASTM International Standard D1593-19, *Standard Specification for*  
854 *Nonrigid Vinyl Chloride Plastic Film and Sheeting*, December 11, 2019, referred to as “ASTM  
855 D1593-19”;

856  
857 (vi) ASTM International Standard D1603-14, *Standard Test Method for*  
858 *Carbon Black Content in Olefin Plastics*, August 1, 2014, referred to as “ASTM D1603-14”;

859  
860 (vii) ASTM International Standard D1790-14, *Standard Test Method for*  
861 *Brittleness Temperature of Plastic Sheeting by Impact*, October 1, 2014, referred to as “ASTM  
862 D1790-14”;

863  
864 (viii) ASTM International Standard D3895-19, *Standard Test Method for*  
865 *Oxidative-Induction Time of Polyolefins by Differential Scanning Calorimetry*, June 25, 2019,  
866 referred to as “ASTM D3895-19”;

867  
868 (ix) ASTM International Standard D4218-15, *Standard Test Method for*  
869 *Determination of Carbon Black Content in Polyethylene Compounds By the Muffle-Furnace*  
870 *Technique*, December 1, 2015, referred to as “ASTM D4218-15”;

871  
872 (x) ASTM International Standard D4833/D4833M-07(2013), *Standard Test*  
873 *Method for Index Puncture Resistance of Geomembranes and Related Products*, May 1, 2013,  
874 referred to as “ASTM D4833/D4833M-07(2013)”;

875

876 (xi) ASTM International Standard D5199-12(2019), *Standard Test Method for*  
877 *Measuring the Nominal Thickness of Geosynthetics*, June 21, 2019, referred to as “ASTM  
878 *D5199-12(2019)*”;

879  
880 (xii) ASTM International Standard D5321/D5321M-20, *Standard Test Method*  
881 *for Determining the Shear Strength of Soil-Geosynthetic and Geosynthetic-Geosynthetic*  
882 *Interfaces by Direct Shear*, March 3, 2020, referred to as “ASTM D5321/D5321M-20”;  
883

884 (xiii) ASTM International Standard D5397-19a, *Standard Test Method for*  
885 *Evaluation of Stress Crack Resistance of Polyolefin Geomembranes Using Notched Constant*  
886 *Tensile Load Test*, October 18, 2019, referred to as “ASTM D5397-19a”;  
887

888 (xiv) ASTM International Standard D5596-03(2016), *Standard Test Method*  
889 *For Microscopic Evaluation of the Dispersion of Carbon Black in Polyolefin Geosynthetics*, June  
890 *1, 2016, referred to as “ASTM D5596-03(2016)”;*  
891

892 (xv) ASTM International Standard D5721-08(2018), *Standard Practice for Air-*  
893 *Oven Aging of Polyolefin Geomembranes*, June 8, 2018, referred to as “ASTM D5721-  
894 *08(2018)”;*  
895

896 (xvi) ASTM International Standard D5885/D5885M-17, *Standard Test Method*  
897 *for Oxidative Induction Time of Polyolefin Geosynthetics by High-Pressure Differential*  
898 *Scanning Calorimetry*, June 1, 2017, referred to as “ASTM D5885/D5885M-17”;  
899

900 (xvii) ASTM International Standard D5887/D5887M-16, *Standard Test Method*  
901 *for Measurement of Index Flux Through Saturated Geosynthetic Clay Liner Specimens Using a*  
902 *Flexible Wall Permeameter*, September 1, 2016, referred to as “ASTM D5887/D5887M-16”;  
903

904 (xviii) ASTM International Standard D5888-19, *Standard Guide for Storage and*  
905 *Handling of Geosynthetic Clay Liners*, May 19, 2019, referred to as “ASTM D5888-19”;  
906

907 (xix) ASTM International Standard D5889/D5889M-18, *Standard Practice for*  
908 *Quality Control of Geosynthetic Clay Liners*, March 9, 2018, referred to as “ASTM  
909 *D5889/D5889M-18”;*  
910

911 (xx) ASTM International Standard D5890-19, *Standard Test Method for Swell*  
912 *Index of Clay Mineral Component of Geosynthetic Clay Liners*, May 30, 2019, referred to as  
913 *“ASTM D5890-19”;*  
914

915 (xxi) ASTM International Standard D5891/D5891M-19, Standard Test Method  
916 for Fluid Loss of Clay Component of Geosynthetic Clay Liners, August 23, 2019, referred to as  
917 “ASTM D5891/D5891M-19”;

918  
919 (xxii) ASTM International Standard D5993-18, Standard Test Method for  
920 Measuring Mass per Unit Area of Geosynthetic Clay Liners, June 15, 2018, referred to as  
921 “ASTM D5993-18”;

922  
923 (xxiii) ASTM International Standard D5994/D5994M-10(2015)e1, Standard Test  
924 Method for Measuring Core Thickness of Textured Geomembranes, May 1, 2015, referred to as  
925 “ASTM D5994/D5994M-10(2015)e1”;

926  
927 (xxiv) ASTM International Standard D6072/D6072M-19, Standard Practice for  
928 Obtaining Samples of Geosynthetic Clay Liners, January 8, 2019, referred to as “ASTM  
929 D6072/D6072M-19”;

930  
931 (xxv) ASTM International Standard D6102-15, Standard Guide for Installation  
932 of Geosynthetic Clay Liners, May 1, 2015, referred to as “ASTM D6102-15”;

933  
934 (xxvi) ASTM International Standard D6243 Standard, Test Method for  
935 Determining the Internal and Interface Shear Strength of Geosynthetic Clay Liner by the Direct  
936 Shear Method, January 1, 2016, referred to as “ASTM D6243”;

937  
938 (xxvii) ASTM International Standard D6243/D6243M-16, Standard Test Method  
939 for Determining the Internal and Interface Shear Strength of Geosynthetic Clay Liner by the  
940 Direct Shear Method, January 1, 2016, referred to as “ASTM D6243/D6243M-16”;

941  
942 (xxviii) ASTM International Standard D6392-12(2018), Standard Test Method for  
943 Determining the Integrity of Nonreinforced Geomembrane Seams Produced Using Thermo-  
944 Fusion Methods, February 15, 2018, referred to as “ASTM D6392-12(2018)”;

945  
946 (xxix) ASTM International Standard D6495/D6495M-18, Standard Guide for  
947 Acceptance Testing Requirements for Geosynthetic Clay Liners, March 9, 2018, referred to as  
948 “ASTM D6495/D6495M-18”;

949  
950 (xxx) ASTM International Standard D6496/D6496M-19, Standard Test Method  
951 for Determining Average Bonding Peel Strength Between Top and Bottom Layers of Needle-  
952 Punched Geosynthetic Clay Liners, May 9, 2019, referred to as “ASTM D6496/D6496M-19”;

953

954 (xxxix) ASTM International Standard D6497/D6497M-02(2015)e1, *Standard*  
955 *Guide for Mechanical Attachment of Geomembrane to Penetrations or Structures*, May 1, 2015,  
956 referred to as “ASTM D6497/D6497M-02(2015)e1”;

957  
958 (xxxix) ASTM International Standard D6693/D6693M-04(2015)e1, *Standard Test*  
959 *Method for Determining Tensile Properties of Nonreinforced Polyethylene and Nonreinforced*  
960 *Flexible Polypropylene Geomembranes*, May 1, 2015, referred to as “ASTM D6693/D6693M-  
961 04(2015)e1”;

962  
963 (xxxix) ASTM International Standard D6768/D6768M-19, *Standard Test Method*  
964 *for Tensile Strength of Geosynthetic Clay Liners*, May 9, 2019, referred to as “ASTM  
965 D6768/D6768M-19”;

966  
967 (xxxix) ASTM International Standard D6788-02(2017), *Standard Specification for*  
968 *Repositionable Pressure-Sensitive Flags*, September 1, 2017, referred to as “ASTM D6788-  
969 02(2017)”;

970  
971 (xxxix) ASTM International Standard D7238-06(2017), *Standard Test Method for*  
972 *Effect of Exposure of Unreinforced Polyolefin Geomembrane Using Fluorescent UV*  
973 *Condensation Apparatus*, July 1, 2017, referred to as “ASTM D7238-06(2017)”;

974  
975 (xxxix) ASTM International Standard D7466/D7466M-10(2015)e1, *Standard Test*  
976 *Method for Measuring Asperity Height of Textured Geomembranes*, May 1, 2015, referred to as  
977 “ASTM D7466/D7466M-10(2015)e1”;

978  
979 (xxxix) ASTM International Standard D751-19, *Standard Test Methods for*  
980 *Coated Fabrics*, May 22, 2019, referred to as “ASTM D751-19”;

981  
982 (xxxix) ASTM International Standard D792-13, *Standard Test Methods for*  
983 *Density and Specific Gravity (Relative Density) of Plastics by Displacement*, November 1, 2013,  
984 referred to as “ASTM D792-13”;

985  
986 (xxxix) ASTM International Standard D814-95(2020), *Standard Test Method for*  
987 *Rubber Property-Vapor Transmission of Volatile Liquids*, February 26, 2020, referred to as  
988 “ASTM D814-95(2020)”;

989  
990 (xxxix) ASTM International Standard D882-18, *Standard Test Method for Tensile*  
991 *Properties of Thin Plastic Sheeting*, August 16, 2018, referred to as “ASTM D882-18”;

992



993 (xxxxxi) Code of Federal Regulations 40 CFR § 261.4(b)(5), in effect as of July 28,  
994 1994, available at: <http://www.ecfr.gov>;

995  
996 (xxxxxii) Geosynthetic Research Institute Standard Specification GRI-  
997 GCL3, Test Methods, Required Properties, and Testing Frequencies of Geosynthetic Clay Liners  
998 (GCLs), as revised on July 26, 2010, referred to as “GRI-GCL3”;

999  
1000 (xxxxxiii) Geosynthetic Research Institute Standard Specification GRI-GM9,  
1001 *Cold Weather Seaming of Geomembranes*, as revised on January 10, 2013, referred to as “GRI-  
1002 GM9”;

1003  
1004 (xxxxxiv) Geosynthetic Research Institute Standard Specification GRI-  
1005 GM13, *Test Methods, Test Properties and Testing Frequency for High Density Polyethylene*  
1006 *(HDPE) Smooth and Textured Geomembranes*, as revised on January 6, 2016, referred to as  
1007 “GRI-GM13”;

1008  
1009 (xxxxxv) *Test Methods for Evaluating Solid Waste: Physical/Chemical*  
1010 *Methods Compendium (SW-846)*, published by the United States Environmental Protection  
1011 Agency, as revised July 2014, referred to as “US EPA SW-846”.

1012  
1013 (b) For these rules incorporated by reference:

1014  
1015 (i) The Environmental Quality Council has determined that incorporation of  
1016 the full text in these rules would be cumbersome or inefficient given the length or nature of the  
1017 rules.

1018  
1019 (ii) This Chapter does not incorporate later amendments or editions of  
1020 incorporated codes, standards, rules, and regulations.

1021  
1022 (iii) All incorporated codes, standards, rules, and regulations are available for  
1023 public inspection at the Department’s Cheyenne office. Contact information for the Cheyenne  
1024 office may be obtained at <http://deq.wyoming.gov> or from (307) 777-7937.